



FLEX Tuneable White

# Flex Tape

P&A's range of flex tape, suitable for a range of applications.

- Available in a wide variety of lengths.
- Various dimming options, including DALI, DMX, etc.
- IP67 rated Tape available for use internally or externally.
- Range of colour temperatures 2700K, 3000K, 4000K & 6000K
- Available with a variety of extruded housings
- 5 Year Guarantee

## Product Code Builder

Type	Description	Code
Product	PALF	PALF
Length	100mm	100
	200mm	200
	500mm	500
	1000mm	1000
	2000mm	2000
Type	IP67 RGB	RGB
	Rigid 100mm	RD
	Standard White	STD
	Tuneable White	TW
Colour Temperature	Incandescent White	2.7K
	Warm White	3K
	Neutral White	4K
	Cool White	6K
Housing	No housing	NH
	Standard	STH
	45° housing	45H
Dimming Options	Fixed Output	FO
	Dali	A1
	DSI	A2
	Switch Dim	A3
	1-10v	A4
	Casambi	A5
DMX	RGB	

**Example Code:** PALF 500 RGB 3K NH FO



IP67 Rated RGB Option



2700K Rigid 100mm



# Flex Tape



Standard Housing



45° Housing

## IP65 RGB

Product	L x W x H (mm)	Ctt Watts	Luminaire / Lumens	LL / CW	Colour Temp	Ra	Colour Consistency	L70 / B10
IP67 RGB	1000 x 11 x 4.5	6.5	209	32	RGB	>80	SDCM 2	>50K

smallest length: 150mm

## RIGID 100mm

Product	L x W x H (mm)	Ctt Watts	Luminaire / Lumens	LL / CW	Colour Temp	Ra	Colour Consistency	L70 / B10
RIGID 100mm	1000 x 11 x 4.5	9	580	63.6	2700K	>80	SDCM 2	>50K

smallest length: 100mm

## Standard White

Product	L x W x H (mm)	Ctt Watts	Luminaire / Lumens	LL / CW	Colour Temp	Ra	Colour Consistency	L70 / B10
Standard White	1000 x 8 x 1.4	7	800	114	3000K	>80	SDCM 2	>60K

smallest length: 50mm

## Tuneable White

Product	L x W x H (mm)	Ctt Watts	Luminaire / Lumens	LL / CW	Colour Temp	Ra	Colour Consistency	L70 / B10
RIGID 100mm	1000 x 8 x 1.45	18.5	2000	108	2700K - 6500K	>80	SDCM 2	>50K

smallest length: 75mm