



PAT-TL125

Slimline LED tubular spotlight mounted on a low profile track adapter.

The low profile track adapter allows for the gear to be near hidden inside of the track. Compatible with Global Trac PRO and Global Trac PULSE from Nordic Aluminum and OneTrack from Stucchi.

- RAL9005 as standard, others available on request
- Available in a choice of beam angles 10°, 30° and 60°.
- Optional Dali Dimming.
- Emergency options available
- Range of colour temperatures 3000K, 4000K & 6000K
- 5 Year Guarantee



Product Code Builder

| Type | Description | Code |
|----------------------|---------------|-------|
| Product | PAT-TL125 | TL125 |
| Delivered Output lms | 1400 | 1400 |
| | Warm White | 3K |
| Colour Temperature | Neutral White | 4K |
| | Cool White | 6K |
| Dimming Options | Fixed Output | FO |
| | Dali | A1 |

Example Code: PAT-TL125 1400 3K A1



PAT-TL125



PAT-TL125

| Product | L x W (mm) | Ctt Watts | Luminaire / Lumens | LL / CW | Colour Temp | Ra | Colour Consistency | L70 / B10 |
|-----------|------------|-----------|--------------------|---------|-------------|-----|--------------------|-----------|
| PAT-TL125 | 172 x 125 | 12.6 | 1400 | 111 | 4000K | >80 | SDCM 2 | >92K |