

TL-TRK

Track

TL-TRK is a slimline LED tubular spotlight mounted on a low profile track. The low profile track adaptor allows for the gear to be hidden inside the track. Compatible with global trac PRO and Global trac PULSE. Available in diameter of 90mm & 125mm and in a range of outputs to suit your needs.

- Efficacy of up to 121 lm/W.
- Colour temperatures: 3000°k, 4000°k
- Colour Finishes: Black (9005) as standard. Other RAL colours, available on request.
- Available in a choice of beam angles 20 °, 30 ° and 50°
- Optional DALI 1-100% dimming.
- Wireless control options: Casambi.
- Standalone Emergency options available

Technical

Product	TL-TRK90 TL-TRK125
Mounting type	Track
Diameters	90 & 125mm
Lumen	1710-2186 Lm
Efficacy	Upto 121 Lm/W
Colour Temperature	Warm White (3K) Neutral White (4K)
Optics	20° 30° 50°
Control	DALI 1-100%, Fixed output, Casambi.
Emergency	Upon request
Rendering	Ra90
IP Rating	IP20
Safety Class	Class 1
MacAdam	SDCM 2
L70/B10	>92K

P&A TL-TRK

Luminaire Order Builder

TL-TRK90 (90mmØ)

STEP 1.	STEP 2.	STEP 3.	STEP 4.	STEP 5.	STEP 6.
Select Current	Optics	CCT	Control	Finish	Emergency
35 350mA 1700 Lm - 14.5W	20 20° Degree beam	3K 3000K	FO Fixed Output	B RAL9005	EM Stand alone emergency track spot available upon request
40 400mA 1943 Lm - 16.6W	30 30° Degree beam	4K 4000K	A1 DALI 1-100% Dim	Z Custom	
	50 50° Degree beam		A5 Casambi		


Example Code: TLTRK9030204KFOB

TL-TRK125 (125mmØ)

STEP 1.	STEP 2.	STEP 3.	STEP 4.	STEP 5.	STEP 6.
Select Current	Optics	CCT	Control	Finish	Emergency
50 500mA 2376 Lm - 20W	20 20° Degree beam	3K 3000K	FO Fixed Output	B RAL9005	EM Stand alone emergency track spot available upon request
55 550mA 2614 Lm - 22W	30 30° Degree beam	4K 4000K	A1 DALI 1-100% Dim	Z Custom	
60 600mA 2851 Lm - 24W	50 50° Degree beam		A5 Casambi		

Example Code: TLTRK12550204KFOB

All electrical and optical data subject to ±10% tolerances.
 Values based on 4000K Colour temperature and CRI90
 CRI80 available on upon request



Dimensions

DØ	L	Finish	Code	Colour Swatch
90	172	Black	9005	
125	172	Custom*	Custom*	

All dimensions are measured in millimetres (mm)

*Custom Colours upon request



IP20
 Protection of fingers against access to hazardous parts, and protection against objects larger than 12.5mm



Safety Class
 Class 1 Safety: chassis is connected to earth with a separate terminal, instead of via the mains cable



Warranty
 5 year Guarantee



Crown House, Plantation Rd, Burscough, Lancashire, L40 8JT
 01704 891333
 sales@pandaprojects.co.uk
 www.pandaprojects.co.uk

Datasheet Code: PA-PAT-TL

CE BS EN60598-1:2015
 ISO 9001 Certification

