



5K

IP44









# ACC

## Surface & Recessed

ACC is a self-contained emergency downlight luminaire, which can be mounted either surface or recessed using the same housing. Operating as either Dali or self-test as standard. Supplied with both open area and corridor lenses.

- Colour temperature: 5000°k.
- Colour Finishes: White or Black as standard.
- · Non Maintained as standard.
- · Supplied with Open area and corridor lenses as standard.
- Lithium Iron Phosphate (LiFe) battery.
- Emergency options: Self-Test or DALI addressable as standard. With 3hr DALI Wireless Sentinel as an optional extra.

#### Technical

Product	ACC			
Mounting type	Surface or Recessed			
Diameter	130mm			
	142mm**			
Lumens	260Lm			
Colour Temperature	Cool White (5K)			
Optics	Corridor			
Optics	Open Area			
Emergency	DALI/ Self-Test (as standard) , 3 hour DALI Wireless Sentinel (Optional)			
Rendering	Ra80+			
IP Rating	IP44			
Safety Class	Class 2			
Led Lifetime	50K			

<sup>\*\*</sup> Surface mounted version only










## Luminaire Order Builder

### ACC

Select mounting	STEP 2. Operation	STEP S. Optics	STEP 4.  CCT	STEP 6. Finish	Emergency
SFR Surface & Recessed	<b>NM</b> Non Maintained 3W - 260Lm	OAC Open Area Lens & Corridor Lens	<b>5K</b> 5000K	<b>W</b> White	<b>EDS</b> DALI & Self-test
				<b>B</b> Black	<b>EW</b> 3 hour DALI Wireless Sentinel

All electrical and optical data subject to  $\pm\,10\%$  tolerances. Values based on 5000K Colour temperature.

Example Code: ACCSFRNMOAC5KWEDS





#### **Dimensions**

Dimensions		Finish	Finish			
DØ	н	RAL	Code	Colour Swatch		
120*	43	White	W			
142**	43	Black	В			

All dimensions are measured in millimetres (mm)

\*Recessed version requires 130mmØ cut out
\*\* Surface mounted version only

## **Emergency spacings**

