



5K

IP20











TS

Surface & Suspended

TS is a twin spot emergency luminaire, with polycarbonate body and lens system, with adjustable beams.

- Colour temperature: 5000°k.
- Colour Finish: White as standard.
- Nickel Cadmium (NiCd) battery.
- Adjustable Heads: For greater control and coverage
- Suspended version: Suspended using chains and additional suspension bracket
- Supplied as Non maintained as standard
- Emergency options: Standard 3hr, Self-Test, DALI addressable or 3hr DALI Wireless Sentinel.

Technical

Product	TS
Mounting type	Surface
	Suspended
Length	275mm
Lumens	2 x 380Lm
Colour Temperature	Day White (5K)
Optics	Clear Lens
Emergency	3 hour, DALI, Self-Test, 3 hour DALI Wireless Sentinel
Rendering	Ra80+
IP Rating	IP20
Safety Class	Class 1
Led Lifetime	50K










Luminaire Order Builder

TS

Select mounting	STEP 2. Operation	STEP 3. Optics	CCT	STEP 5. Finish	Emergency
SF Surface CS Chain Suspended	NM Non maintained 2 x 3W - 2 x 380lm	CL Twin Clear Lens	5K 5000K	W White	E3 Standard 3 Hour ED DALI/EMPRO ES Self-Test
					EW 3 hour DALI Wireless Sentinel

All electrical and optical data subject to \pm 10% tolerances.

Example Code: TSSFNMCL5KWE3





Dimensions	Finish

L	w	н	RAL	Code	Colour Swatch
350	120	90	White	W	

All dimensions are measured in millimetres (mm)

Ancillaries

 	images

Wire Suspensions	Code
1m Chain suspension kit	TS-CS-1M
2m Chain suspension kit	TS-CS-2M
3m Chain suspension kit	TS-CS-3M
4m Chain suspension kit	TS-CS-4M









