





3K 4K 2.7-5.7K

IP20



BH3

Surface

BH3 is a sleek wall mounted bed head luminaire, designed for healthcare faculties, with no visible fixings, where dust and dirt can build up, providing a smooth easy to clean surface. Supplied as Direct/indirect as standard.

- Efficacy of up to 114 lm/W.
- Colour temperatures: 3000°k, 4000°k or Tunable White (2700°K - 5700°K).
- Colour Finishes: White (9016), Black (9005) or Silver (9006). Other RAL colours, available on request.
- Dimming options: DALI 1-100%*.
- Wireless control options: Casambi.
- Emergency options: Standard 3hr, Self-Test, Dali addressable or 3Hr Dali Wireless Sentinel.
- Maximum combined milliamp must not exceed 850mA total.

Technical

Product	BH3
Mounting type	Surface
Standard Length	600mm
Lumen	925 - 5200 Lm**
Efficacy	Upto 114 lm/W
Colour Temperature	Warm White (3K) Neutral White (4K) Tunable white (2.7K-5.7K)
Optics	Microprism + Opal diffuser (Direct/Indirect)
Control	DALI 1-100%, Casambi,
Emergency	3 hour, DALI, Self-Test, DALI Wireless Sentinel
Rendering	Ra80+
IP Rating	IP20
Safety Class	Class 1
MacAdam	SDCM 3
L70/B10	>50K
Weight	3.7kg

* 1 x DALI Dual channel driver fitted as standard

** Individual lumens figures, Combined figures must not exceed 6000 lumens.

P&A BH3


Luminaire Order Builder

BH3

STEP 1. Select Direct Current	STEP 2. Select Indirect Current	STEP 3. CCT	STEP 4. Control	STEP 5. Finish	STEP 6. Emergency
D15 150mA 925 Lm Downlight Microprism Diffuser 8W D20 200mA 1233 Lm Downlight Microprism Diffuser 11W D30 300mA 1849 Lm Downlight Microprism Diffuser 16.5W D40 400mA 2466 Lm Downlight Microprism Diffuser 22W D50 500mA 3082 Lm Downlight Microprism Diffuser 27W D60 600mA 3699 Lm Downlight Microprism Diffuser 33W D70 700mA 4315 Lm Downlight Microprism Diffuser 38W	U15 150mA 1128 Lm Uplight Opal Diffuser 8W U20 200mA 1504 Lm Uplight Opal Diffuser 11W U30 300mA 2255 Lm Uplight Opal Diffuser 16.5W U40 400mA 3007 Lm Uplight Opal Diffuser 22W U50 500mA 3759 Lm Uplight Opal Diffuser 27W U60 600mA 4511 Lm Uplight Opal Diffuser 33W U70 700mA 5200 Lm Uplight Opal Diffuser 38W	3K 3000K 4K 4000K TW 2700K - 5700K Tunable white	A1 DALI 1-100% Dim Dual channel driver A5 Casambi	W RAL9016M B RAL9005 S RAL9006 Z Custom	E3 Standard 3 Hour ED DALI/EMPRO ES Self-Test EW 3 hour DALI Wireless Sentinel

All electrical and optical data subject to $\pm 10\%$ tolerances.
 Values based on 4000K Colour temperature.
 Combined mA cannot exceed 850mA total.
 6000 Lumens maximum based on combined mA settings.
 Wattage figures above do not include driver losses.

Example Code: BH3D50U354KA1WE3



Dimensions

L	W	H
600	221	38

All dimensions are measured in millimetres (mm)

Finish

RAL	Code	Colour Swatch
White	9016	
Black	9005	
Silver	9006	
Custom*	Custom*	

*Custom Colours upon request



Crown House, Plantation Rd, Burscough, Lancashire, L40 8JT
 01704 891333
 sales@pandaprojects.co.uk
 www.pandaprojects.co.uk



Datasheet Code: PA-10551-0



P&A BH3


Wall Bracket

Fixing details



Distribution Type

Direct/Indirect



IP20
IP20
Protection of fingers against access to hazardous parts, and protection against objects larger than 12.5mm



Safety Class
Class I Safety chassis is connected to earth with a separate terminal, instead of via the mains cable



Warranty
5 year Guarantee