




3K 4K

IP65



EM3



# TRI-X

## Wall Mounted

TRI-X, is a modern exterior wall mounted luminaire, providing a high quality of light efficacy. Housing fabricated from Heavy duty steel fitted with durable polycarbonate diffuser, gasket sealed front frame secured with anti tamper screws. Dark Sky Compliant.

- Efficacy of up to 104 lm/W.
- Colour temperatures: 3000°k or 4000°k.
- Colour Finishes: White (9016), Black (9005) or Silver (9006). Other RAL colours, available on request.
- Optic: Type II/III for pedestrian paths\*
- Dimming options: DALI 1-100% Dim, DSI, Switch Dim, 1-10v
- Wireless control options: Casambi.
- Dark Sky compliant with 0%ULR.
- Emergency options: Standard 3hr, Self-Test, Dali addressable or 3hr Dali Wireless Sentinel.

### Technical

Product	TRI-X
Mounting type	Wall Mounted
Dimension	215mm x 320mm
Lumen	1351 - 1788 Lm
Efficacy	Upto 104 lm/W
Colour Temperature	Warm White (3K) Neutral White (4K)
Optic	Type II/III
Control	DALI 1-100%, DSI, 1-10V, Casambi, Fixed output,
Emergency	3 hour, DALI, Self-Test, DALI Wireless Sentinel
Rendering	Ra70+
IP Rating	IP65
Safety Class	Class 1
MacAdam	SDCM 3
L70/B10	>50K

\*Other Optics available, Please contact P&A technical department for more details.


## Luminaire Order Builder

### TRI-X

STEP 1. Select Current	STEP 2. Optics	STEP 3. CCT	STEP 4. Control	STEP 5. Finish	STEP 6. Emergency
<b>50</b> 500mA 1351 Lm - 13W  <b>60</b> 600mA 1597 Lm - 15.8W  <b>65</b> 650mA 1685 Lm - 16.8W  <b>70</b> 700mA 1788 Lm - 18.1W	<b>CL</b> Type II/III For pedestrian paths	<b>3K</b> 3000K  <b>4K</b> 4000K	<b>FO</b> Fixed Output  <b>A1</b> DALI 1-100% Dim  <b>A2</b> DSI  <b>A3</b> Switch Dim  <b>A4</b> 1-10v  <b>A5</b> Casambi	<b>W</b> RAL9016M  <b>B</b> RAL9005  <b>S</b> RAL9006  <b>Z</b> Custom	<b>E3</b> Standard 3 Hour  <b>ED</b> DALI/EMPRO  <b>ES</b> Self-Test  <b>EW</b> 3 hour DALI Wireless Sentinel

All electrical and optical data subject to ±10% tolerances.  
Values based on 4000K Colour temperature and DALI driver.

Example Code: TRIX50CL4KFOB



#### Dimensions

L	W	H	Finish	Code	Colour Swatch
215	215	320	White	9016	
			Black	9005	
			Silver	9006	
			Custom*	Custom*	

All dimensions are measured in millimetres (mm)

\*Custom Colours upon request



IP65  
Protection against dust and solid objects. Water jets from any angle (12.5mm nozzle)



Safety Class  
Class 1 Safety: chassis is connected to earth with a separate terminal, instead of via the mains cable



Warranty  
5 year Guarantee