

3K

4K

IP20



TL-TRK50

Track

TL-TRK50 is a beautiful balanced and precisely proportioned addition to our TL-TRK range of spotlights. With its minimalist 57mm x 110mm LED tubular housing, delivers perfect lighting quality and harmony. Compatible with global trac PRO and Global trac PULSE.

- Efficacy of up to 130 lm/W.
- Colour temperatures: 2700°k, 3000°k or 4000°k.
- Colour Finishes: Black (9005) as standard. Other RAL colours, available on request.
- Available in a choice of beam angles 12°, 24° and 36°.
- Dimming options: DALI 1-100%.
- Wireless control options: Casambi.
- Standalone Emergency options available.

Technical

Product	TL-TRK50
Mounting type	Track
Diameters	57mm
Lumen	1130-1535 Lm
Efficacy	Up to 130 lm/W
Colour Temperature	Soft White (27K)
	Warm White (3K)
	Neutral White (4K)
Optics	12°
	24°
	36°
Control	DALI 1-100%, Fixed output, Casambi.
Emergency	Standalone EM upon request
Rendering	Ra90
IP Rating	IP20
Safety Class	Class 1
MacAdam	SDCM 3
L70/B10	>50K

P&A TL-TRK50



Luminaire Order Builder

TL-TRK50

STEP 1.	STEP 2.	STEP 3.	STEP 4.	STEP 5.	STEP 6.
Select Current	Optics	CCT	Control	Finish	Emergency
25 250mA 1130 Lm - 8.5W 35 350mA 1535 Lm - 12W	12* 12° degree beam 24 24° degree beam 36 36° degree beam	27K 2700K 3K 3000K 4K 4000K	FO Fixed Output A1 DALI 1-100% Dim A5 Casambi	B RAL9005 + Black Reflector Z Custom	EM Stand alone emergency track spot available upon request

All electrical and optical data subject to ± 10% tolerances.
 Values based on 4000K Colour temperature, 36° Beam and
 CRI90.

Example Code: TLTRK5035364KFOB



Dimensions

DØ	L	Finish	Code	Colour Swatch
57	110	RAL		
		Black	9005	
		Custom*	Custom*	

All dimensions are measured in millimetres (mm)

*Custom Colours upon request

