



3K

4K

IP20



TL-TRK90

Track

TL-TRK90 is a slimline LED tubular spotlight mounted on a low profile track. The low profile track adaptor allows for the gear to be hidden inside the track. Compatible with global trac PRO and Global trac PULSE. Available in diameter of 90mm and in a range of outputs to suit your needs.

- Efficacy of up to 131 lm/W.
- Colour temperatures: 3000°k, 4000°k
- Colour Finishes: Black (9005) as standard. Other RAL colours, available on request.
- Available in a choice of beam angles 20°, 30° and 50°
- Optional DALI 1-100% dimming.
- Wireless control options: Casambi.
- Standalone Emergency options available

Technical

Product	TL-TRK90
Mounting type	Track
Diameters	90mm
Lumen	1646-1881 Lm
Efficacy	Upto 131 Lm/W
Colour Temperature	Warm White (3K) Neutral White (4K)
Optics	20° 30° 50°
Control	DALI 1-100%, Fixed output, Casambi.
Emergency	Upon request
Rendering	Ra80
IP Rating	IP20
Safety Class	Class 1
MacAdam	SDCM 3
L70/B10	>92K


P&A TL-TRK90

Luminaire Order Builder

TL-TRK90 (90mmØ)

STEP 1.	STEP 2.	STEP 3.	STEP 4.	STEP 5.	STEP 6.
Select Current	Optics	CCT	Control	Finish	Emergency
35 350mA 1646 Lm - 12.6W 40 400mA 1881 Lm - 14.4W	20 20° Degree beam 30 30° Degree beam 50 50° Degree beam	3K 3000K 4K 4000K	FO Fixed Output A1 DALI 1-100% Dim A5 Casambi	B RAL9005 Z Custom	EM Stand alone emergency track spot available upon request

Example Code: TLTRK9030204KFOB



Dimensions

DØ	L	Finish	Code	Colour Swatch
90	172	Black	9005	
		Custom*	Custom*	

All dimensions are measured in millimetres (mm)

*Custom Colours upon request

IP20

IP20
Protection of fingers against access to hazardous parts, and protection against objects larger than 12.5mm



Safety Class
Class 1 Safety, chassis is connected to earth with a separate terminal, instead of via the mains cable



Warranty
5 year Guarantee



Crown House, Plantation Rd, Burscough, Lancashire, L40 8JT
 01704 891333
 sales@pandaprojects.co.uk
 www.pandaprojects.co.uk

Datasheet Code: PA-PAT-TL



BS EN60598-1:2015
ISO 9001 Certification

