



27K

3K

4K

IP20



TL-TRK50

Track

TL-TRK50 is a beautiful balanced and precisely proportioned addition to our TL-TRK range of spotlights. With its minimalist 57mm x 110mm LED tubular housing, delivers perfect lighting quality and harmony. Compatible with global trac PRO and Global trac PULSE.

- Efficacy of up to 130 lm/W.
- Colour temperatures: 2700°k, 3000°k or 4000°k.
- Colour Finishes: Black (9005) as standard. Other RAL colours, available on request.
- Available in a choice of beam angles 12°, 24° and 36°.
- Dimming options: DALI 1-100%.
- Wireless control options: Casambi.
- Standalone Emergency options available.

Technical

| | |
|--------------------|-------------------------------------|
| Product | TL-TRK50 |
| Mounting type | Track |
| Diameters | 57mm |
| Lumen | 1130-1535 Lm |
| Efficacy | Up to 130 lm/W |
| Colour Temperature | Soft White (27K) |
| | Warm White (3K) |
| | Neutral White (4K) |
| Optics | 12° |
| | 24° |
| | 36° |
| Control | DALI 1-100%, Fixed output, Casambi. |
| Emergency | Standalone EM upon request |
| Rendering | Ra90 |
| IP Rating | IP20 |
| Safety Class | Class 1 |
| MacAdam | SDCM 3 |
| L70/B10 | >50K |

P&A TL-TRK50



Luminaire Order Builder

TL-TRK50

| STEP 1. | STEP 2. | STEP 3. | STEP 4. | STEP 5. | STEP 6. |
|---|---|---|--|--|---|
| Select Current | Optics | CCT | Control | Finish | Emergency |
| 25 250mA 1130 Lm - 8.5W 35 350mA 1535 Lm - 12W | 12* 12° degree beam 24 24° degree beam 36 36° degree beam | 27K 2700K 3K 3000K 4K 4000K | FO Fixed Output A1 DALI 1-100% Dim A5 Casambi | B RAL9005 + Black Reflector Z Custom | EM Stand alone emergency track spot available upon request |

All electrical and optical data subject to ± 10% tolerances.
 Values based on 4000K Colour temperature, 36° Beam and
 CRI90.

Example Code: TLTRK5035364KFOB



Dimensions

| DØ | L | Finish | Code | Colour Swatch |
|----|-----|---------|---------|---------------|
| 57 | 110 | RAL | | |
| | | Black | 9005 | |
| | | Custom* | Custom* | |

All dimensions are measured in millimetres (mm)

*Custom Colours upon request



IP20
 Protection of fingers against
 access to hazardous parts, and
 protection against objects larger
 than 12.5mm



Safety Class
 Class 1 Safety, chassis is
 connected to earth with a
 separate terminal, instead of via
 the mains cable



Warranty
 5 year Guarantee



Crown House, Plantation Rd, Burscough, Lancashire, L40 8JT
 01704 891333
 sales@pandaprojects.co.uk
 www.pandaprojects.co.uk

Datasheet Code: PA-10792-16



BS EN60598-1:2015
 ISO 9001 Certification

